

---

# **mdutils Documentation**

*Release 1.3.1*

**Dídac Coll**

**Oct 18, 2021**



---

## Contents:

---

<b>1 Overview</b>	<b>1</b>
<b>2 Features</b>	<b>3</b>
<b>3 Installation</b>	<b>5</b>
<b>4 Markdown File Example</b>	<b>7</b>
<b>5 Python Code of Markdown File Example</b>	<b>11</b>
<b>6 mdutils</b>	<b>21</b>
<b>7 Indices and tables</b>	<b>37</b>
<b>Python Module Index</b>	<b>39</b>
<b>Index</b>	<b>41</b>



# CHAPTER 1

---

## Overview

---

This Python package contains a set of basic tools that can help to create a markdown file while running a Python code. Thus, if you are executing a Python code and you save the result in a text file, Why not format it? So using files such as Markdown can give a great look to those results. In this way, mdutils will make things easy for creating Markdown files.



There are some different features available on that version of mdutils:

### 2.1 Writing and Reading Files

- Write and Read Markdown files.
- Append data to the end of a Markdown file.
- Use markers to place text.

### 2.2 Markdown

- Implemented method to give format to the text: bold, italics, change color. . .
- Add headers of levels 1 til 6 (atx style) or 1 and 2 (setext style).
- Create tables.
- Create a table of contents.
- Add Links.
- Add Markdown Images.
- Add Html Images.

---

**Note:** Some available features will depend on which CSS you are using. For example, GitHub does not allow to give color to text.

---





## CHAPTER 3

---

### Installation

---

Use pip to install mdutils:

```
$ pip install mdutils
```



---

## Markdown File Example

---

### 4.1 Contents

- *Overview*
- *This is what you can do*
  - *Create Markdown files*
  - *Create Headers*
  - *Table of Contents*
  - *Paragraph and Text Format*
  - *Create a Table*

### 4.2 Overview

This is an example of markdown file created using mdutils python package. In this example you are going to see how to create a markdown file using this library. Moreover, you're finding the available features which makes easy the creation of this type of files while you are running Python code.

---

**Note:** Some features available on this library have no effect with the GitHub Markdown CSS. Some of them are: coloring text, centering text. . .

---

## 4.3 This is what you can do

### 4.3.1 Create Markdown files

```
import Mdutils

mdFile = MdUtils(file_name='Example_Markdown',title='Markdown File Example')
mdFile.create_md_file()
```

---

**Note:** `create_md_file()` is the last command that has to be called.

---

### 4.3.2 Create Headers

Using `new_header` method you can create headers of different levels depending on the style. There are two available styles: 'atx' and 'setext'. The first one has til 6 different header levels. Atx's levels 1 and 2 are automatically added to the table of contents unless the parameter `add_table_of_contents` is set to 'n'. The 'setext' style only has two levelsof headers.

```
mdFile.new_header(level=1, title='Atx Header 1')
mdFile.new_header(level=2, title='Atx Header 2')
mdFile.new_header(level=3, title='Atx Header 3')
mdFile.new_header(level=4, title='Atx Header 4')
mdFile.new_header(level=5, title='Atx Header 5')
mdFile.new_header(level=6, title='Atx Header 6')
```

## 4.4 Atx Header 1

### 4.4.1 Atx Header 2

**Atx Header 3**

**Atx Header 4**

**Atx Header 5**

Atx Header 6

```
mdFile.new_header(level=1, title='Setext Header 1', style='setext')
mdFile.new_header(level=2, title='Setext Header 2', style='setext')
```

## 4.5 Setext Header 1

### 4.5.1 Setext Header 2

### 4.5.2 Table of Contents

If you have defined some headers of level 1 and 2, you can create a table of contents invoking the following command (Normally, the method will be called at the end of the code before calling `create_md_file()`)

```
mdFile.new_table_of_contents(table_title='Contents', depth=2)
```

### 4.5.3 Paragraph and Text Format

mdutils allows you to create paragraph, line breaks or simply write text:

#### New Paragraph Method

```
mdFile.new_paragraph("Using ``new_paragraph`` method you can very easily add a new_
↳paragraph"
                    " This example of paragraph has been added using this method.
↳Moreover,"
                    "``new_paragraph`` method make your live easy because it can_
↳give format"
                    " to the text. Lets see an example:")
```

Using `new_paragraph` method you can very easily add a new paragraph on your markdown file. This example of paragraph has been added using this method. Moreover, `new_paragraph` method make your live easy because it can give format to the text. Lets see an example:

```
mdFile.new_paragraph("This is an example of text in which has been added color, bold_
↳and italics text.", bold_italics_code='bi', color='purple')
```

#### New Line Method

mdutils has a method which can create new line breaks. Lets see it.

```
mdFile.new_line("This is an example of line break which has been created with ``new_
↳line`` method.")
```

This is an example of line break which has been created with `new_line` method.

As `new_paragraph`, `new_line` allows users to give format to text using `bold_italics_code` and `color` parameters:

```
mdFile.new_line("This is an inline code which contains bold and italics text and it_
↳is centered", bold_italics_code='cib', align='center')
```

## Write Method

write method writes text in a markdown file without jump lines '\n' and as new\_paragraph and new\_line, you can give format to text using the arguments bold\_italics\_code, color and align:

```
mdFile.write("The following text has been written with ``write`` method. You can use_  
↳markdown directives to write:"  
    "**bold**", _italics_, ``inline_code``... or ")  
mdFile.write("use the following available parameters: \n")
```

The following text has been written with write method. You can use markdown directives to write: **bold**, *italics*, inline\_code... or use the following available parameters:

```
mdFile.write(' \n')  
mdFile.write('bold_italics_code', bold_italics_code='bic')  
mdFile.write(' \n')  
mdFile.write('Text color', color='green')  
mdFile.write(' \n')  
mdFile.write('Align Text to center', align='center')
```

## 4.5.4 Create a Table

The library implements a method called new\_table that can create tables using a list of strings. This method only needs: the number of rows and columns that your table must have. Optionally you can align the content of the table using the parameter text\_align

```
list_of_strings = ["Items", "Descriptions", "Data"]  
for x in range(5):  
    list_of_strings.extend(["Item " + str(x), "Description Item " + str(x), str(x)])  
mdFile.new_line()  
mdFile.new_table(columns=3, rows=6, text=list_of_strings, text_align='center')
```

Items	Descriptions	Data
Item 0	Description Item 0	0
Item 1	Description Item 1	1
Item 2	Description Item 2	2
Item 3	Description Item 3	3
Item 4	Description Item 4	4

---

## Python Code of Markdown File Example

---

```

# Python
#
# This file implements an example.
#
# This file is part of mdutils. https://github.com/didix21/mdutils
#
# MIT License: (C) 2018 Didac Coll

from mdutils.mdutils import MdUtils
from mdutils import Html

mdFile = MdUtils(file_name='Example_Markdown', title='Markdown File Example')

mdFile.new_header(level=1, title='Overview') # style is set 'atx' format by default.

mdFile.new_paragraph("This is an example of markdown file created using mdutils,
↳python package. In this example you "
↳"are going to see how to create a markdown file using this
↳library. Moreover, you're "
↳"finding the available features which makes easy the creation of
↳this type of files while you "
↳"are running Python code.")
mdFile.new_paragraph("**IMPORTANT:** some features available on this library have no
↳effect with the GitHub Markdown "
↳"CSS. Some of them are: coloring text, centering text...")
mdFile.new_paragraph()

# Available Features
mdFile.new_header(level=1, title="This is what you can do")

#
↳*****
# ***** Markdown
↳*****

```

(continues on next page)

(continued from previous page)

```

#
↳ *****
mdFile.new_header(level=2, title="Create Markdown files")
mdFile.new_paragraph("`create_md_file()` is the last command that has to be called.
↳ ")
mdFile.insert_code("import Mdutils\n"
                    "\n"
                    "\n"
                    "mdFile = MdUtils(file_name='Example_Markdown',title='Markdown_
↳ File Example')\n"
                    "mdFile.create_md_file()", language='python')

#
↳ *****
# ***** Headers
↳ *****
#
↳ *****
mdFile.new_header(level=2, title="Create Headers")
mdFile.new_paragraph("Using `new_header` method you can create headers of different
↳ levels depending on the style. "
                    "There are two available styles: 'atx' and 'setext'. The first
↳ one has til 6 different header "
                    "levels. Atx's levels 1 and 2 are automatically added to the
↳ table of contents unless the "
                    "parameter `add_table_of_contents` is set to 'n'. The 'setext'
↳ style only has two levels"
                    "of headers.")

mdFile.insert_code("mdFile.new_header(level=1, title='Atx Header 1')\n"
                    "mdFile.new_header(level=2, title='Atx Header 2')\n"
                    "mdFile.new_header(level=3, title='Atx Header 3')\n"
                    "mdFile.new_header(level=4, title='Atx Header 4')\n"
                    "mdFile.new_header(level=5, title='Atx Header 5')\n"
                    "mdFile.new_header(level=6, title='Atx Header 6')", language=
↳ 'python')

mdFile.new_header(level=1, title='Atx Header 1', add_table_of_contents='n')
mdFile.new_header(level=2, title='Atx Header 2', add_table_of_contents='n')
mdFile.new_header(level=3, title='Atx Header 3')
mdFile.new_header(level=4, title='Atx Header 4')
mdFile.new_header(level=5, title='Atx Header 5')
mdFile.new_header(level=6, title='Atx Header 6')

mdFile.insert_code("mdFile.new_header(level=1, title='Setext Header 1', style='setext
↳ ')\n"
                    "mdFile.new_header(level=2, title='Setext Header 2', style='setext
↳ ')", language='python')

mdFile.new_header(level=1, title='Setext Header 1', style='setext', add_table_of_
↳ contents='n')
mdFile.new_header(level=2, title='Setext Header 2', style='setext', add_table_of_
↳ contents='n')
mdFile.new_paragraph() # Add two jump lines

#
↳ *****

```

(continues on next page)



(continued from previous page)

```

# ***** Create a table of contents
↳*****
#
↳*****
mdFile.new_header(level=2, title='Table of Contents')
mdFile.new_paragraph("If you have defined some headers of level 1 and 2, you can
↳create a table of contents invoking "
    "the following command (Normally, the method will be called at
↳the end of the code before calling "
    "`create_md_file()``")
mdFile.insert_code("mdFile.new_table_of_contents(table_title='Contents', depth=2)",
↳language='python')

#
↳*****
# ***** Paragraph and Text format
↳*****
#
↳*****
mdFile.new_header(level=2, title="Paragraph and Text Format")
mdFile.new_paragraph("mdutils allows you to create paragraph, line breaks or simply
↳write text:")
# ***** Paragraph
↳*****
mdFile.new_header(3, "New Paragraph Method")

mdFile.insert_code("mdFile.new_paragraph(\"Using ``new_paragraph`` method you can
↳very easily add a new paragraph\" \n"
    "\t\t\t\t\t \" This example of paragraph has been added using this
↳method. Moreover, \"\n"
    "\t\t\t\t\t \" ``new_paragraph`` method make your live easy because
↳it can give format\" \n"
    "\t\t\t\t\t \" to the text. Lets see an example:\")", language=
↳'python')

mdFile.new_paragraph("Using ``new_paragraph`` method you can very easily add a new
↳paragraph on your markdown file. "
    "This example of paragraph has been added using this method.
↳Moreover, ``new_paragraph`` method "
    "make your live easy because it can give format to the text.
↳Lets see an example:")

mdFile.insert_code("mdFile.new_paragraph(\"This is an example of text in which has
↳been added color, "
    "bold and italics text.\", bold_italics_code='bi', color='purple')
↳", language='python')

mdFile.new_paragraph("This is an example of text in which has been added color, bold
↳and italics text.",
    bold_italics_code='bi', color='purple')
# ***** New Line
↳*****
mdFile.new_header(3, "New Line Method")

mdFile.new_paragraph("``mdutils`` has a method which can create new line breaks. Lets
↳see it.")
mdFile.insert_code("mdFile.new_line(\"This is an example of line break which has been
↳created with ``new_line`` \"

```

(continues on next page)

(continued from previous page)

```

        "method.\n"), language='python')
mdFile.new_line("This is an example of line break which has been created with ``new_
↳line`` method.")
mdFile.new_paragraph("As ``new_paragraph``, ``new_line`` allows users to give format_
↳to text using "
        "``bold_italics_code`` and ``color`` parameters:")

mdFile.insert_code("mdFile.new_line(\nThis is an inline code which contains bold and_
↳italics text and it is centered\n",
        " bold_italics_code='cib', align='center')", language='python')

mdFile.new_line("This is an inline code which contains bold and italics text and it_
↳is centered",
        bold_italics_code='cib', align='center')
# ***** write_
↳*****
mdFile.new_header(3, "Write Method")
mdFile.new_paragraph("``write`` method writes text in a markdown file without jump_
↳lines ``\n`` and as "
        "``new_paragraph`` and ``new_line``, you can give format to text_
↳using the arguments "
        "``bold_italics_code``, ``color`` and ``align``: ")

mdFile.insert_code("mdFile.write(\nThe following text has been written with ``write``_
↳method. You can use markdown "
        "directives to write:\n\n"
        "\t\t\t \n**bold**, _italics_, ``inline_code``... or \n)\n"
        "mdFile.write(\nuse the following available parameters: \n\n)",
↳language='python')

mdFile.write("\n\nThe following text has been written with ``write`` method. You can_
↳use markdown directives to write: "
        "``**bold**``, _italics_, ``inline_code``... or ")
mdFile.write("use the following available parameters: \n\n")

mdFile.insert_code("mdFile.write(' \n')\n"
        "mdFile.write('bold_italics_code', bold_italics_code='bic')\n"
        "mdFile.write(' \n')\n"
        "mdFile.write('Text color', color='green')\n"
        "mdFile.write(' \n')\n"
        "mdFile.write('Align Text to center', align='center')", language=
↳'python')

mdFile.write(' \n')
mdFile.write('bold_italics_code', bold_italics_code='bic')
mdFile.write(' \n')
mdFile.write('Text color', color='green')
mdFile.write(' \n')
mdFile.write('Align Text to center', align='center')
mdFile.write(' \n')

#_
↳*****
# ***** Create a Table_
↳*****
#_
↳*****

```

(continues on next page)

(continued from previous page)

```

mdFile.new_header(2, "Create a Table")
mdFile.new_paragraph("The library implements a method called ``new_table`` that can
↳ create tables using a list of "
                    "strings. This method only needs: the number of rows and columns,
↳ that your table must have. "
                    "Optionally you can align the content of the table using the
↳ parameter ``text_align``")

mdFile.insert_code("list_of_strings = [\"Items\\", \"Descriptions\\", \"Data\\"]\n"
                  "for x in range(5):\n"
                  "\tlist_of_strings.extend([\"Item \" + str(x), \"Description Item \" +
↳ str(x), str(x)])\n"
                  "mdFile.new_line()\n"
                  "mdFile.new_table(columns=3, rows=6, text=list_of_strings, text_
↳ align='center')", language='python')

list_of_strings = ["Items", "Descriptions", "Data"]
for x in range(5):
    list_of_strings.extend(["Item " + str(x), "Description Item " + str(x), str(x)])
mdFile.new_line()
mdFile.new_table(columns=3, rows=6, text=list_of_strings, text_align='center')

#
↳ *****
# ***** Create Link
↳ *****
#
↳ *****

mdFile.new_header(2, "Create Links")

# ***** Inline link
↳ *****

mdFile.new_header(3, "Create inline links")

link = "https://github.com/didix21/mdutils"
text = "mdutils"

mdFile.new_paragraph("``new_inline_link`` method allows you to create a link of the
↳ style: "
                    "``[mdutils](https://github.com/didix21/mdutils)``.\n")
mdFile.new_paragraph("Moreover, you can add bold, italics or code in the link text.
↳ Check the following examples: \n")

mdFile.insert_code("mdFile.new_line(' - Inline link: ' "
                  " + mdFile.new_inline_link(link='{ }', text='{ }')) \n".format(link,
↳ text) +
                  "mdFile.new_line(' - Bold inline link: ' "
                  "+ mdFile.new_inline_link(link='{ }', text='{ }', bold_italics_code=
↳ 'b') \n".format(link, text) +
                  "mdFile.new_line(' - Italics inline link: ' "
                  "+ mdFile.new_inline_link(link='{ }', text='{ }', bold_italics_code=
↳ 'i') \n".format(link, text) +
                  "mdFile.new_line(' - Code inline link: ' "
                  "+ mdFile.new_inline_link(link='{ }', text='{ }', bold_italics_code=
↳ 'i') \n".format(link, text) +

```

(continues on next page)

(continued from previous page)

```

        "mdFile.new_line(' - Bold italics code inline link: ' "
        "+ mdFile.new_inline_link(link='{}', text='{}', bold_italics_code=
↪'cbi') \n".format(link, text) +
        "mdFile.new_line(' - Another inline link: ' + mdFile.new_inline_
↪link(link='{}') \n".format(link),
        language='python')

mdFile.new_line(' - Inline link: ' + mdFile.new_inline_link(link=link, text=text))
mdFile.new_line(' - Bold inline link: ' + mdFile.new_inline_link(link=link,
↪text=text, bold_italics_code='b'))
mdFile.new_line(' - Italics inline link: ' + mdFile.new_inline_link(link=link,
↪text=text, bold_italics_code='i'))
mdFile.new_line(' - Code inline link: ' + mdFile.new_inline_link(link=link,
↪text=text, bold_italics_code='c'))
mdFile.new_line(
    ' - Bold italics code inline link: ' + mdFile.new_inline_link(link=link,
↪text=text, bold_italics_code='cbi'))
mdFile.new_line(' - Another inline link: ' + mdFile.new_inline_link(link=link))

# ***** Reference link
↪*****
mdFile.new_header(3, "Create reference links")

mdFile.new_paragraph("`new_reference_link` method allows you to create a link of
↪the style: "
        "`[mdutils][1]`. All references will be added at the end of
↪the markdown file automatically as: \n")

mdFile.insert_code("[1]: https://github.com/didix21/mdutils", language="python")
mdFile.new_paragraph("Lets check some examples: \n")

link = "https://github.com/didix21/mdutils"

mdFile.insert_code("mdFile.write('\n - Reference link: ' "
        "+ mdFile.new_reference_link(link='{}', text='mdutils', reference_
↪tag='1')\n".format(link) +
        "mdFile.write('\n - Reference link: ' "
        "+ mdFile.new_reference_link(link='{}', text='another reference',
↪reference_tag='md')\n".format(
        link) +
        "mdFile.write('\n - Bold link: ' "
        "+ mdFile.new_reference_link(link='{}', text='Bold reference',
↪reference_tag='bold', bold_italics_code='b')\n".format(
        link) +
        "mdFile.write('\n - Italics link: ' "
        "+ mdFile.new_reference_link(link='{}', text='Bold reference',
↪reference_tag='italics', bold_italics_code='i')\n".format(
        link),
        language="python")

mdFile.write("\n - Reference link: " + mdFile.new_reference_link(link=link, text=
↪'mdutils', reference_tag='1'))
mdFile.write(
    "\n - Reference link: " + mdFile.new_reference_link(link=link, text='another
↪reference', reference_tag='md'))
mdFile.write("\n - Bold link: " + mdFile.new_reference_link(link=link, text='Bold
↪reference', reference_tag='bold',

```

(continues on next page)

(continued from previous page)

```

                                                                 bold_italics_code='b'))
mdFile.write(
    "\n - Italics link: " + mdFile.new_reference_link(link=link, text='Italics_
↳reference', reference_tag='italics',
                                                                 bold_italics_code='i'))

#_
↳*****
# ***** Create Lists_
↳*****
#_
↳*****
mdFile.new_header(2, "Create Lists")
# ***** Unordered Lists_
↳*****
mdFile.new_header(3, "Create unordered lists")
mdFile.new_paragraph(
    "You can add Mark down unordered list using ``mdFile.new_list(items, marked_
↳with)``. Lets check an example: ")
items = ["Item 1", "Item 2", "Item 3", "Item 4", ["Item 4.1", "Item 4.2", ["Item 4.2.1
↳", "Item 4.2.2"],
                                                                 "Item 4.3", ["Item 4.3.1"]], "Item 5
↳"]
mdFile.insert_code(f'items = {items}\n'
                  f'mdFile.new_list(items)\n')
mdFile.new_list(items=items)

# ***** Ordered Lists_
↳*****
mdFile.new_header(3, "Create ordered lists")
mdFile.new_paragraph("You can add ordered ones easily, too: ``mdFile.new_list(items,
↳marked_with='1')``")
mdFile.new_list(items=items, marked_with='1')

mdFile.new_paragraph("Moreover, you can add mixed list, for example: ")
items = ["Item 1", "Item 2", ["1. Item 2.1", "2. Item 2.2"], "Item 3"]
mdFile.insert_code(f'items = {items}\n'
                  f'mdFile.new_list(items)\n')
mdFile.new_list(items)
mdFile.new_paragraph("Maybe you want to replace the default hyphen ``-`` by a ``+``_
↳or ``*`` then you can do: "
                    "``mdFile.new_list(items, marked_with='*')``.")

#_
↳*****
# ***** Add Images_
↳*****
#_
↳*****

mdFile.new_header(2, "Add images")

# ***** Inline Image_
↳*****

image_text = "snow trees"
path = "./doc/source/images/photo-of-snow-covered-trees.jpg"

```

(continues on next page)

(continued from previous page)

```

mdFile.new_header(3, "Inline Images")

mdFile.new_paragraph("You can add inline images using ``new_inline_image`` method.
↳Method will return: "
                    "` `[image](../path/to/your/image.png)``. Check the following
↳example: ")
mdFile.insert_code("mdFile.new_line(mdFile.new_inline_image(text='{}', path='{}'))".
↳format(image_text, path))
mdFile.new_line(mdFile.new_inline_image(text=image_text, path=path))

# ***** Reference Image
↳*****
mdFile.new_header(3, "Reference Images")
mdFile.new_paragraph("You can add inline images using ``new_reference_image`` method.
↳Method will return: "
                    "` `[image][im]``. Check the following example: ")
mdFile.insert_code(
    "mdFile.new_line(mdFile.new_reference_image(text='{}', path='{}', reference_tag=
↳'im'))".format(image_text, path))
mdFile.new_line(mdFile.new_reference_image(text=image_text, path=path, reference_tag=
↳'im'))

# ***** Html Image
↳*****

mdFile.new_header(2, "Add HTML images")

# ***** Size Image
↳*****

mdFile.new_header(3, "Change size to images")
path = "./doc/source/images/sunset.jpg"

mdFile.new_paragraph("With ``Html.image`` you can change size of images in a markdown
↳file. For example you can do"
                    "the following for changing width: ``mdFile.new_paragraph(Html.
↳image(path=path, size='200')``")

mdFile.new_paragraph(Html.image(path=path, size='200'))

mdFile.new_paragraph(
    "Or maybe only want to change height: ``mdFile.new_paragraph(Html.image(path=path,
↳size='x300')``")
mdFile.new_paragraph(Html.image(path=path, size='x300'))

mdFile.new_paragraph("Or change width and height: ``mdFile.new_paragraph(Html.
↳image(path=path, size='300x300')``")
mdFile.new_paragraph(Html.image(path=path, size='300x300'))
mdFile.write('\n')

# ***** Align Image
↳*****

mdFile.new_header(3, "Align images")
mdFile.new_paragraph("Html.image allow to align images, too. For example you can run:
↳")

```

(continues on next page)

(continued from previous page)

```
        "`mdFile.new_paragraph(Html.image(path=path, size='300x200', ↵
↵align='center'))`")
mdFile.new_paragraph(Html.image(path=path, size='300x200', align='center'))

# Create a table of contents
mdFile.new_table_of_contents(table_title='Contents', depth=2)
mdFile.create_md_file()
```





## 6.1 mdutils package

### 6.1.1 Subpackages

#### `mdutils.fileutils` package

#### Submodules

#### `mdutils.fileutils.fileutils` module

**class** `mdutils.fileutils.fileutils.MarkDownFile` (*name*=")

Bases: `object`

`MarkDownFile` class creates a new file of MarkDown extension.

#### Features available are:

- Create a file.
- Rewrite a file with new data.
- Write at the end of the file.

**append\_after\_second\_line** (*data*)

Write after the file's first line.

**Parameters** *data* (*str*) – is a string containing all the data that is written in the markdown file.

**append\_end** (*data*)

Write at the last position of a Markdown file.

**Parameters** *data* (*str*) – is a string containing all the data that is written in the markdown file.

**static read\_file** (*file\_name*)

Read a Markdown file using a file name. It is not necessary to add \*.md extension.

**Parameters** **file\_name** (*str*) – Markdown file's name.

**Returns** return all file's data.

**Return type** str

**rewrite\_all\_file** (*data*)

Rewrite all the data of a Markdown file by data.

**Parameters** **data** (*str*) – is a string containing all the data that is written in the markdown file.

## Module contents

### mdutils.tools package

#### Submodules

#### mdutils.tools.Header module

**class** mdutils.tools.Header.**Header**

Bases: object

Contain the main methods to define Headers on a Markdown file.

#### Features available:

- Create Markdown Titles: *atx* and *setext* formats are available.
- Create Header Hanchors.
- Auto generate a table of contents.
- Create Tables.
- **Bold**, *italics*, `inline_code` text converters.
- Align text to center.
- Add color to text.

**static atx\_level\_1** (*title*)

Return a atx level 1 header.

**Parameters** **title** (*str*) – text title.

**Returns** a header title of form: '\n#' + title + '\n'

**Return type** str

**static atx\_level\_2** (*title*)

Return a atx level 2 header.

**Parameters** **title** (*str*) – text title.

**Returns** a header title of form: '\n##' + title + '\n'

**Return type** str

**static atx\_level\_3** (*title*)

Return a atx level 3 header.

**Parameters** `title` (*str*) – text title.

**Returns** a header title of form: `'\n###' + title + '\n'`

**Return type** `str`

**static** `atx_level_4` (*title*)

Return a atx level 4 header.

**Parameters** `title` (*str*) – text title.

**Returns** a header title of form: `'\n####' + title + '\n'`

**Return type** `str`

**static** `atx_level_5` (*title*)

Return a atx level 5 header.

**Parameters** `title` (*str*) – text title.

**Returns** a header title of form: `'\n#####' + title + '\n'`

**Return type** `str`

**static** `atx_level_6` (*title*)

Return a atx level 6 header.

**Parameters** `title` (*str*) – text title.

**Returns** a header title of form: `'\n#####' + title + '\n'`

**Return type** `str`

**static** `choose_header` (*level*, *title*, *style='atx'*)

This method choose the style and the header level.

### Examples

```
>>> from mdutils.tools.Header import Header
>>> Header.choose_header(level=1, title='New Header', style='atx')
'\n# New Header\n'
```

```
>>> Header.choose_header(level=2, title='Another Header 1', style=
↳ 'setext')
'\nAnother Header 1\n-----\n'
```

### Parameters

- **level** – Header Level, For Atx-style 1 til 6. For Setext-style 1 and 2 header levels.
- **title** – Header Title.
- **style** – Header Style atx or setext.

### Returns

**static** `header_anchor` (*text*, *link=""*)

Creates an internal link of a defined Header level 1 or level 2 in the markdown file.

Giving a text string an text link you can create an internal link of already existing header. If the link string does not contain '#', it will creates an automatic link of the type #title-1.

### Parameters

- **text** (*str*) – it is the text that will be displayed.

- **link** (*str*) – it is the internal link.

**Returns** '[text] (#link)'

**Return type** string

**Example:** [Title 1](#title-1)

**static setext\_level\_1** (*title*)

Return a setext level 1 header.

**Parameters** **title** (*str*) – text title.

**Returns** a header title of form: '\n' + title + '\n=====\\n'.

**Return type** str

**static setext\_level\_2** (*title*)

Return a setext level 1 header.

**Parameters** **title** (*str*) – text title.

**Returns** a header title of form: '\n' + title + '\n-----\\n'.

**Return type** str

## mdutils.tools.Html module

**class** mdutils.tools.Html.**Html**

Bases: object

**classmethod** **image** (*path: str, size: str = None, align: str = None*) → str

**Parameters**

- **path** (*str*) –
- **size** (*str*) – (In px) for width write '<int>', for height write 'x<int>' or width and height '<int>x<int>'.
- **align** (*str*) – can be 'left', 'center' or 'right'.

**Returns** html format

**Return type** str

**Example**

```
>>> Html.image(path='../image.jpg', size='200', align='center')
>>> Html.image(path='../image.jpg', size='x200', align='left')
>>> Html.image(path='../image.jpg', size='300x400')
```

**static** **paragraph** (*text: str, align: str = None*) → str

**Parameters**

- **text** –
- **align** (*str*) – center or right.

**Returns** "<p align=\"{}\">\n {}\\n</p>".format(align, text).

**Return type** str

**class** mdutils.tools.Html.**HtmlSize**

Bases: object

**classmethod** `size_to_width_and_height` (*size: str*) → str

**exception** `mdutils.tools.Html.SizeBadFormat` (*message*)

Bases: Exception

Raise exception when size does not match the expected format

## mdutils.tools.Image module

**class** `mdutils.tools.Image.Image` (*reference*)

Bases: object

**static** `new_inline_image` (*text, path, tooltip=None*)

### Parameters

- **text** (*str*) – Text that is going to be displayed in the markdown file as a iamge.
- **path** (*str*) – Image’s path / link.
- **tooltip** (*str*) –

**Returns** return the image in markdown format `![ + text + ']( + path + 'tooltip' + ')'`.

**Return type** str

**new\_reference\_image** (*text, path, reference\_tag=None, tooltip=None*)

### Parameters

- **text** (*str*) – Text that is going to be displayed in the markdown file as a image.
- **path** (*str*) – Image’s path / link.
- **reference\_tag** (*str*) – Tag that will be placed at the end of the markdown file jointly with the image’s path.
- **tooltip** (*str*) –

**Returns** return the image in markdown format `![ + text + '][ + reference_tag + ']'`.

**Return type** str

## mdutils.tools.Link module

**class** `mdutils.tools.Link.Inline`

Bases: object

**static** `new_link` (*link, text=None, tooltip=None*)

### Parameters

- **link** (*str*) –
- **text** (*str*) – Text that is going to be displayed in the markdown file as a link.
- **tooltip** (*str*) – Add a tool tip on the image.

**Returns** `'[ + text + ']( + link + 'tooltip' + ')` or if link is only defined: `< + link >`.

**Return type** str

**class** `mdutils.tools.Link.Reference`

Bases: `object`

**get\_references** ()

**Returns**

**Return type** `dict`

**get\_references\_as\_markdown** ()

**Returns**

**Return type** `str`

**new\_link** (*link*, *text*, *reference\_tag=None*, *tooltip=None*)

**Parameters**

- **link** (*str*) –
- **text** (*str*) – Text that is going to be displayed in the markdown file as a link.
- **reference\_tag** (*str*) – Reference that will be saved on reference dict.
- **tooltip** (*str*) – Add a tooltip on the link.

**Returns** '[' + *text* + '][' + *reference\_tag* + ']' or if *reference\_tag* is not defined: '[' + *text* + ']'

**Return type** `str`

## mdutils.tools.MDList module

**class** `mdutils.tools.MDList.MDCheckbox` (*items: [<class 'str'>], checked: bool = False*)

Bases: `mdutils.tools.MDList.MDListHelper`

This class allows to create checkbox Markdown list.

**get\_md** () → `str`

**class** `mdutils.tools.MDList.MDList` (*items: [<class 'str'>], marked\_with: str = '-'*)

Bases: `mdutils.tools.MDList.MDListHelper`

This class allows to create unordered or ordered Markdown list.

**get\_md** () → `str`

Get the list in markdown format.

**Returns**

**Return type** `str`

**class** `mdutils.tools.MDList.MDListHelper`

Bases: `object`

## mdutils.tools.Table module

**class** `mdutils.tools.Table.Table`

Bases: `object`

**create\_table** (*columns: int*, *rows: int*, *text: [<class 'str'>]*, *text\_align: Union[str, list, None] = None*)

This method takes a list of strings and creates a table.

Using arguments `columns` and `rows` allows to create a table of  $n$  columns and  $m$  rows. The `columns * rows` operations has to correspond to the number of elements of `text` list argument.

### Parameters

- **columns** (*int*) – number of columns of the table.
- **rows** (*int*) – number of rows of the table.
- **text** (*list of str*) – a list of strings.
- **text\_align** (*str\_or\_list*) – text align argument. Values available are: 'right', 'center', 'left' and None (default). If `text_align` is a list then individual alignment can be set for each column.

**Returns** a markdown table.

**Return type** str

### Example

```
>>> from mdutils.tools.Table import Table
>>> text_list = ['List of Items', 'Description', 'Result', 'Item 1',
↳ 'Description of item 1', '10', 'Item 2', 'Description of item 2', '0']
>>> table = Table().create_table(columns=3, rows=3, text=text_list, text_
↳ align='center')
>>> print(repr(table))
'\n|List of Items|Description|Result|\n| :---: | :---: | :---: |\n|Item_
↳ 1|Description of item 1|10|\n|Item 2|Description of item 2|0|\n'
```

Table 1: Table result on Markdown

List of Items	Description	Results
Item 1	Description of Item 1	10
Item 2	Description of Item 2	0

## mdutils.tools.TableOfContents module

**class** mdutils.tools.TableOfContents.**TableOfContents**

Bases: object

**create\_table\_of\_contents** (*array\_of\_title\_contents, depth=1*)

This method can create a table of contents using an array of the different titles. The depth can be changed.  
:param array\_of\_title\_contents: a string list with the different headers. :type array\_of\_title\_contents: list  
:param depth: allows to include atx headers 1 through 6. Possible values: 1, 2, 3, 4, 5, or 6. :type depth: int  
:return: return a string ready to be written to a Markdown file. :rtype: str

## mdutils.tools.TextUtils module

**class** mdutils.tools.TextUtils.**TextUtils**

Bases: object

This class helps to create bold, italics and change color text.

**static add\_tooltip** (*link, tip*)

**Parameters**

- **link** (*str*) –
- **tip** (*str*) –

return: link + " " + format + " "

**static bold** (*text*)

Bold text converter.

**Parameters** **text** (*str*) – a text string.

**Returns** a string like this example: '\*\*\*text\*\*'

**Return type** str

**static center\_text** (*text*)

Place a text string to center.

**Parameters** **text** (*str*) – a text string.

**Returns** a string like this example: '<center>text</center>'

**static inline\_code** (*text*)

Inline code text converter.

**Parameters** **text** (*str*) – a text string.

**Returns** a string like this example: '`text`'

**Return type** str

**static insert\_code** (*code*, *language=""*)

This method allows to insert a piece of code.

**Parameters** **code** – code string.

:type code:str :param language: code language: python. c++, c#. ... :type language: str :return: markdown style. :rtype: str

**static italics** (*text*)

Italics text converter.

**Parameters** **text** (*str*) – a text string.

**Returns** a string like this example: '\_text\_'

**Return type** str

**static text\_color** (*text*, *color='black'*)

Change text color.

**Parameters**

- **text** (*str*) – it is the text that will be changed its color.
- **color** (*str*) – it is the text color: 'orange', 'blue', 'red'... or a **RGB** color such as '#ffce00'.

**Returns** a string like this one: '<font color='color'>'text'</font>'

**Return type** str

**static text\_external\_link** (*text*, *link=""*)

Using this method can be created an external link of a file or a web page.

**Parameters**



- **text** (*str*) – Text to be displayed.
- **link** (*str*) – External Link.

**Returns** return a string like this: '[Text to be shown](https://write.link.com)'

**Return type** str

**static text\_format** (*text*, *bold\_italics\_code=""*, *color='black'*, *align=""*)

Text format helps to write multiple text format such as bold, italics and color.

**Parameters**

- **text** (*str*) – it is a string in which will be added the new format
- **bold\_italics\_code** (*str*) – using 'b': bold, 'i': \_italics\_ and 'c': *inline\_code*.
- **color** (*str*) – Can change text color. For example: 'red', 'green', 'orange'...
- **align** (*str*) – Using this parameter you can align text.

**Returns** return a string with the new text format.

**Return type** str

**Example**

```
>>> from mdutils.tools.TextUtils import TextUtils
>>> TextUtils.text_format(text='Some Text Here', bold_italics_code='bi',
↳color='red', align='center')
'***<center><font color="red">Some Text Here</font></center>***'
```

## Module contents

### 6.1.2 Submodules

### 6.1.3 mdutils.mdutils module

Module **mdutils**

**The available features are:**

- Create Headers, Til 6 sub-levels.
- Auto generate a table of contents.
- Create List and sub-list.
- Create paragraph.
- Generate tables of different sizes.
- Insert Links.
- Insert Code.
- Place text anywhere using a marker.

**class** mdutils.mdutils.**MdUtils** (*file\_name*, *title=""*, *author=""*)

Bases: object

This class give some basic methods that helps the creation of Markdown files while you are executing a python code.

The `__init__` variables are:

- **file\_name:** it is the name of the Markdown file.
- **author:** it is the author fo the Markdown file.
- **header:** it is an instance of Header Class.
- **textUtils:** it is an instance of TextUtils Class.
- **title:** it is the title of the Markdown file. It is written with Setext-style.
- **table\_of\_contents:** it is the table of contents, it can be optionally created.
- **file\_data\_text:** contains all the file data that will be written on the markdown file.

**create\_marker** (*text\_marker*)

This will add a marker to `file_data_text` and returns the marker result in order to be used whenever you need.

Markers allows to place them to the string data text and they can be replaced by a peace of text using `place_text_using_marker` method.

**Parameters** `text_marker` (*str*) – marker name.

**Returns** return a marker of the following form: `'##--[ '+ text_marker + ' ]--##'`

**Return type** str

**create\_md\_file** ()

It creates a new Markdown file. :return: return an instance of a MarkDownFile.

**get\_md\_text** () → str

Instead of writing the markdown text into a file it returns it as a string.

**Returns** return a string with the markdown text.

**insert\_code** (*code*, *language=""*)

This method allows to insert a peace of code on a markdown file.

**Parameters**

- **code** (*str*) – code string.
- **language** (*str*) – code language: python, c++, c#...

**Returns**

**Return type** str

**new\_checkbox\_list** (*items: [<class 'str'>]*, *checked: bool = False*)

Add checkbox list in MarkDown file.

**Parameters**

- **items** (*[str]*) – Array of items for generating the checkbox list.
- **checked** (*bool*) – if you set this to True. All checkbox will be checked. By default is False.

**Returns**

**new\_header** (*level*, *title*, *style='atx'*, *add\_table\_of\_contents='y'*)

Add a new header to the Markdown file.

**Parameters**

- **level** (*int*) – Header level. *atx* style can take values 1 til 6 and *setext* style take values 1 and 2.
- **title** (*str*) – Header title.
- **style** (*str*) – Header style, can be 'atx' or 'setext'. By default 'atx' style is chosen.
- **add\_table\_of\_contents** (*str*) – by default the atx and setext headers of level 1 and 2 are added to the table of contents, setting this parameter to 'n'.

### Example

```
>>> from mdutils import MdUtils
>>> mdfile = MdUtils("Header_Example")
>>> print(mdfile.new_header(level=2, title='Header Level 2 Title', style='atx'
↳', add_table_of_contents='y'))
'\n## Header Level 2 Title\n'
>>> print(mdfile.new_header(level=2, title='Header Title', style='setext'))
'\nHeader Title\n-----\n'
```

### **static new\_inline\_image** (*text, path*)

Add inline images in a markdown file. For example [MyImage] (../MyImage.jpg).

#### Parameters

- **text** (*str*) – Text that is going to be displayed in the markdown file as a iamge.
- **path** (*str*) – Image's path / link.

**Returns** return the image in markdown format '! [ + text + ' ] ( ' + path + ' ) '.

**Return type** str

### **new\_inline\_link** (*link, text=None, bold\_italics\_code="", align=""*)

Creates a inline link in markdown format.

#### Parameters

- **link** (*str*) –
- **text** (*str*) – Text that is going to be displayed in the markdown file as a link.
- **bold\_italics\_code** (*str*) – Using 'b': **bold**, 'i': *italics* and 'c': inline\_code...
- **align** (*str*) – Using this parameter you can align text. For example 'right', 'left' or 'center'.

**Returns** returns the link in markdown format '[ + text + ' ] ( ' + link + ' ) '. If text is not defined returns '<' + link + '>'.

**Return type** str

---

**Note:** If param text is not provided, link param will be used instead.

---

### **new\_line** (*text="", bold\_italics\_code="", color='black', align="", wrap\_width=120*)

Add a new line to Markdown file. The text is saved to the global variable file\_data\_text.

#### Parameters

- **text** (*str*) – is a string containing the paragraph text. Optionally, the paragraph text is returned.

- **bold\_italics\_code** (*str*) – using 'b': **bold**, 'i': *italics* and 'c': *inline\_code*...
- **color** (*str*) – Can change text color. For example: 'red', 'green', 'orange'...
- **align** (*str*) – Using this parameter you can align text. For example 'right', 'left' or 'center'.
- **wrap\_width** (*int*) – wraps text with designated width by number of characters. By default, long words are not broken. Use width of 0 to disable wrapping.

**Returns** return a string '\n' + *text*. Not necessary to take it, if only has to be written to the file.

**Return type** str

**new\_list** (*items*: [*<class 'str'>*], *marked\_with*: *str* = '-')

Add unordered or ordered list in Markdown file.

#### Parameters

- **items** (*[str]*) – Array of items for generating the list.
- **marked\_with** (*str*) – By default has the value of '-', can be '+', '\*'. If you want to generate an ordered list then set to '1'.

**Returns**

**new\_paragraph** (*text*=", *bold\_italics\_code*=", *color*='black', *align*=", *wrap\_width*=120)

Add a new paragraph to Markdown file. The text is saved to the global variable *file\_data\_text*.

#### Parameters

- **text** (*str*) – is a string containing the paragraph text. Optionally, the paragraph text is returned.
- **bold\_italics\_code** (*str*) – using 'b': **bold**, 'i': *italics* and 'c': *inline\_code*.
- **color** (*str*) – Can change text color. For example: 'red', 'green', 'orange'...
- **align** (*str*) – Using this parameter you can align text.
- **wrap\_width** (*int*) – wraps text with designated width by number of characters. By default, long words are not broken. Use width of 0 to disable wrapping.

**Returns** '\n\n' + *text*. Not necessary to take it, if only has to be written to the file.

**Return type** str

**new\_reference\_image** (*text*, *path*, *reference\_tag*=None)

Add reference images in a markdown file. For example [MyImage] [*my\_image*]. All references will be stored at the end of the markdown file.

#### Parameters

- **text** (*str*) – Text that is going to be displayed in the markdown file as a image.
- **path** (*str*) – Image's path / link.
- **reference\_tag** (*str*) – Tag that will be placed at the end of the markdown file jointly with the image's path.

**Returns** return the image in markdown format '! [+ *text* + '][ + *reference\_tag* + ']'.

**Return type** str

---

**Note:** If param `reference_tag` is not provided, `text` param will be used instead.

---

**new\_reference\_link** (*link*, *text*, *reference\_tag=*`None`, *bold\_italics\_code=*`"`, *align=*`"`)

Creates a reference link in markdown format. All references will be stored at the end of the markdown file.

#### Parameters

- **link** (*str*) –
- **text** (*str*) – Text that is going to be displayed in the markdown file as a link.
- **reference\_tag** (*str*) – Tag that will be placed at the end of the markdown file jointly with the link.
- **bold\_italics\_code** (*str*) – Using `'b': bold`, `'i': italics` and `'c': inline_code...`
- **align** (*str*) – Using this parameter you can align text. For example `'right'`, `'left'` or `'center'`.

**Returns** returns the link in markdown format `'[ + text + ][' + link + ]'`.

**Return type** `str`

---

**Note:** If param `reference_tag` is not provided, `text` param will be used instead.

---

#### Example

```
>>> from mdutils import MdUtils
>>> md = MdUtils("Reference link")
>>> link = md.new_reference_link(link='https://github.com', text='github',
↳reference_tag='git')
>>> md.new_link(link)
>>> print(repr(link))
'[github][git]'
>>> link = md.new_reference_link(link='https://github.com/didix21/mdutils',
↳text='mdutils')
>>> md.new_link(link)
>>> print(repr(link))
'[mdutils]'
>>> link = md.new_line(md.new_reference_link(link='https://github.com/didix21/
↳mdutils', text='mdutils', reference_tag='md', bold_italics_code='b'))
>>> md.new_link(link)
>>> print(repr(link))
'[*mdutils*][md]'
>>> md.create_md_file()
```

**new\_table** (*columns*, *rows*, *text*, *text\_align=*`'center'`, *marker=*`"`)

This method takes a list of strings and creates a table.

Using arguments `columns` and `rows` allows to create a table of  $n$  columns and  $m$  rows. The `columns * rows` operations has to correspond to the number of elements of `text` list argument. Moreover, argument allows to place the table wherever you want from the file.

#### Parameters

- **columns** (*int*) – this variable defines how many columns will have the table.

- **rows** (*int*) – this variable defines how many rows will have the table.
- **text** (*list*) – it is a list containing all the strings which will be placed in the table.
- **text\_align** (*str*) – allows to align all the cells to the 'right', 'left' or 'center'. By default: 'center'.
- **marker** (*str*) – using `create_marker` method can place the table anywhere of the markdown file.

**Returns** can return the table created as a string.

**Return type** `str`

**Example**

```
>>> from mdutils import MdUtils
>>> md = MdUtils(file_name='Example')
>>> text_list = ['List of Items', 'Description', 'Result', 'Item 1',
↳ 'Description of item 1', '10', 'Item 2', 'Description of item 2', '0']
>>> table = md.new_table(columns=3, rows=3, text=text_list, text_align='center'
↳ ')
>>> print(repr(table))
'\n|List of Items|Description|Result|\n| :---: | :---: | :---: |\n|Item_
↳ |Description of item 1|10|\n|Item 2|Description of item 2|0|\n'
```

Table 2: Table result on Markdown

List of Items	Description	Results
Item 1	Description of Item 1	10
Item 2	Description of Item 2	0

**new\_table\_of\_contents** (*table\_title='Table of contents', depth=1, marker=""*)

Table of contents can be created if Headers of 'atx' style have been defined.

This method allows to create a table of contents and define a title for it. Moreover, *depth* allows user to define how many levels of headers will be placed in the table of contents. If no marker is defined, the table of contents will be placed automatically after the file's title.

**Parameters**

- **table\_title** (*str*) – The table content's title, by default "Table of contents"
- **depth** (*int*) – allows to include atx headers 1 through 6. Possible values: 1, 2, 3, 4, 5, or 6.
- **marker** (*str*) – allows to place the table of contents using a marker.

**Returns** a string with the data is returned.

**Return type** `str`

**place\_text\_using\_marker** (*text, marker*)

It replace a previous marker created with `create_marker` with a text string.

This method is going to search for the *marker* argument, which has been created previously using `create_marker` method, in *file\_data\_text* string.

**Parameters**

- **text** (*str*) – the new string that will replace the marker.

- **marker** (*str*) – the marker that has to be replaced.

**Returns** return a new `file_data_text` with the replace marker.

**Return type** `str`

**read\_md\_file** (*file\_name*)

Reads a Markdown file and save it to global class `file_data_text`.

**Parameters** **file\_name** (*str*) – Markdown file's name that has to be read.

**Returns** optionally returns the file data content.

**Return type** `str`

**write** (*text=""*, *bold\_italics\_code=""*, *color='black'*, *align=""*, *marker=""*, *wrap\_width=120*)

Write text in `file_Data_text` string.

**Parameters**

- **text** (*str*) – a text a string.
- **bold\_italics\_code** (*str*) – using 'b': **bold**, 'i': *italics* and 'c': `inline_code...`
- **color** (*str*) – Can change text color. For example: 'red', 'green', 'orange'...
- **align** (*str*) – Using this parameter you can align text. For example 'right', 'left' or 'center'.
- **wrap\_width** (*int*) – wraps text with designated width by number of characters. By default, long words are not broken. Use width of 0 to disable wrapping.
- **marker** (*str*) – allows to replace a marker on some point of the file by the text.

## 6.1.4 Module contents





## CHAPTER 7

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`



## m

- `mdutils`, 35
- `mdutils.fileutils`, 22
- `mdutils.fileutils.fileutils`, 21
- `mdutils.mdutils`, 29
- `mdutils.tools`, 29
  - `mdutils.tools.Header`, 22
  - `mdutils.tools.Html`, 24
  - `mdutils.tools.Image`, 25
  - `mdutils.tools.Link`, 25
  - `mdutils.tools.MDList`, 26
  - `mdutils.tools.Table`, 26
  - `mdutils.tools.TableOfContents`, 27
  - `mdutils.tools.TextUtils`, 27



**A**

add\_tooltip() (*mdutils.tools.TextUtils.TextUtils static method*), 27

append\_after\_second\_line() (*mdutils.fileutils.fileutils.MarkDownFile method*), 21

append\_end() (*mdutils.fileutils.fileutils.MarkDownFile method*), 21

atx\_level\_1() (*mdutils.tools.Header.Header static method*), 22

atx\_level\_2() (*mdutils.tools.Header.Header static method*), 22

atx\_level\_3() (*mdutils.tools.Header.Header static method*), 22

atx\_level\_4() (*mdutils.tools.Header.Header static method*), 23

atx\_level\_5() (*mdutils.tools.Header.Header static method*), 23

atx\_level\_6() (*mdutils.tools.Header.Header static method*), 23

**B**

bold() (*mdutils.tools.TextUtils.TextUtils static method*), 28

**C**

center\_text() (*mdutils.tools.TextUtils.TextUtils static method*), 28

choose\_header() (*mdutils.tools.Header.Header static method*), 23

create\_marker() (*mdutils.mdutils.MdUtils method*), 30

create\_md\_file() (*mdutils.mdutils.MdUtils method*), 30

create\_table() (*mdutils.tools.Table.Table method*), 26

create\_table\_of\_contents() (*mdutils.tools.TableOfContents.TableOfContents method*), 27

**G**

get\_md() (*mdutils.tools.MDList.MDCheckbox method*), 26

get\_md() (*mdutils.tools.MDList.MDList method*), 26

get\_md\_text() (*mdutils.mdutils.MdUtils method*), 30

get\_references() (*mdutils.tools.Link.Reference method*), 26

get\_references\_as\_markdown() (*mdutils.tools.Link.Reference method*), 26

**H**

Header (*class in mdutils.tools.Header*), 22

header\_anchor() (*mdutils.tools.Header.Header static method*), 23

Html (*class in mdutils.tools.Html*), 24

HtmlSize (*class in mdutils.tools.Html*), 24

**I**

Image (*class in mdutils.tools.Image*), 25

image() (*mdutils.tools.Html.Html class method*), 24

Inline (*class in mdutils.tools.Link*), 25

inline\_code() (*mdutils.tools.TextUtils.TextUtils static method*), 28

insert\_code() (*mdutils.mdutils.MdUtils method*), 30

insert\_code() (*mdutils.tools.TextUtils.TextUtils static method*), 28

italics() (*mdutils.tools.TextUtils.TextUtils static method*), 28

**M**

MarkDownFile (*class in mdutils.fileutils.fileutils*), 21

MDCheckbox (*class in mdutils.tools.MDList*), 26

MDList (*class in mdutils.tools.MDList*), 26

MDListHelper (*class in mdutils.tools.MDList*), 26

MdUtils (*class in mdutils.mdutils*), 29

mdutils (*module*), 35

mdutils.fileutils (*module*), 22

mdutils.fileutils.fileutils (*module*), 21

mdutils.mdutils (*module*), 29

`mdutils.tools` (*module*), 29  
`mdutils.tools.Header` (*module*), 22  
`mdutils.tools.Html` (*module*), 24  
`mdutils.tools.Image` (*module*), 25  
`mdutils.tools.Link` (*module*), 25  
`mdutils.tools.MDList` (*module*), 26  
`mdutils.tools.Table` (*module*), 26  
`mdutils.tools.TableOfContents` (*module*), 27  
`mdutils.tools.TextUtils` (*module*), 27

## N

`new_checkbox_list()` (*mdutils.mdutils.MdUtils method*), 30  
`new_header()` (*mdutils.mdutils.MdUtils method*), 30  
`new_inline_image()` (*mdutils.mdutils.MdUtils static method*), 31  
`new_inline_image()` (*mdutils.tools.Image.Image static method*), 25  
`new_inline_link()` (*mdutils.mdutils.MdUtils method*), 31  
`new_line()` (*mdutils.mdutils.MdUtils method*), 31  
`new_link()` (*mdutils.tools.Link.Inline static method*), 25  
`new_link()` (*mdutils.tools.Link.Reference method*), 26  
`new_list()` (*mdutils.mdutils.MdUtils method*), 32  
`new_paragraph()` (*mdutils.mdutils.MdUtils method*), 32  
`new_reference_image()` (*mdutils.mdutils.MdUtils method*), 32  
`new_reference_image()` (*mdutils.tools.Image.Image method*), 25  
`new_reference_link()` (*mdutils.mdutils.MdUtils method*), 33  
`new_table()` (*mdutils.mdutils.MdUtils method*), 33  
`new_table_of_contents()` (*mdutils.mdutils.MdUtils method*), 34

## P

`paragraph()` (*mdutils.tools.Html.Html static method*), 24  
`place_text_using_marker()` (*mdutils.mdutils.MdUtils method*), 34

## R

`read_file()` (*mdutils.fileutils.fileutils.MarkDownFile static method*), 21  
`read_md_file()` (*mdutils.mdutils.MdUtils method*), 35  
`Reference` (*class in mdutils.tools.Link*), 25  
`rewrite_all_file()` (*mdutils.fileutils.fileutils.MarkDownFile method*), 22

## S

`setext_level_1()` (*mdutils.tools.Header.Header static method*), 24  
`setext_level_2()` (*mdutils.tools.Header.Header static method*), 24  
`size_to_width_and_height()` (*mdutils.tools.Html.HtmlSize class method*), 24  
`SizeBadFormat`, 25

## T

`Table` (*class in mdutils.tools.Table*), 26  
`TableOfContents` (*class in mdutils.tools.TableOfContents*), 27  
`text_color()` (*mdutils.tools.TextUtils.TextUtils static method*), 28  
`text_external_link()` (*mdutils.tools.TextUtils.TextUtils static method*), 28  
`text_format()` (*mdutils.tools.TextUtils.TextUtils static method*), 29  
`TextUtils` (*class in mdutils.tools.TextUtils*), 27

## W

`write()` (*mdutils.mdutils.MdUtils method*), 35